

MAHARASHTRA STATE ELECTRICITY TRANSMISSION CO., LTD.

PAC Division, Chatrapati Sambhajinagar.

wing No 3, Ground Floor,

Administrative Building Mahatransco, 132kV Harsool S/s Premises, Jalgaon Road, Harsool, Chatrapati Sambhajinagar

Contact No:0240-2348351(O), 2331097

E-mail Id:eeabdtel@gmail.com,ee2510@mahatransco.in

EE/PAC/CSN/TS/L-1/ NO 0 0 0 1 9

Date: 1 9 JAN 2024

E-Enquiry

Sub: We are inviting sealed and firm quotations for the supply of one Executive table (big) and two Executive Mid Back Chairs under the PAC Division, Chatrapati Sambhajinagar. Please find Schedule "A" enclosed herewith for detailed specifications.

Terms and Conditions:

- 1. Quotations must reach our office on or before 29/01/2024, by 17:30 hrs, and will be opened on the same day if possible.
- 2. The works should be completed within 7 days from the date of the issue of the order.
- 3. Rates validity should remain valid for 90 days.
- 4. The earliest possible completion period will be appreciated.
- 5. The quoted price should include transportation to our office address, and no additional charges will be paid for it.
- 6. Kindly provide your GST registration number in the quotation.
- 7. Required Documents:
- a) Valid Shop Act license
- b) Copy of PAN Card
- c) GST Registration Certificate
- d) Experience Certificate
- 8. The undersigned reserves the right to reject any or all quotations without assigning any reason.
- 9. Please super scribe the quotation with "Quotation towards Supply of Executive Table (1 qty) and Executive Mid Back Chairs (2 qty), under PAC Division, Chatrapati Sambhajinagar."

10. Furniture should be dispatched to the following address:

Executive Engineer,

Wing No 3, Ground Floor,

Administrative Building Mahatransco,

132kV Harsool S/s Premises, Jalgaon Road, Harsool, Chatrapati Sambhajinagar Your prompt attention to this matter is appreciated.

Encl:1. Schedule "A"

Shashikant S Kulkarni Executive Engineer,

PAC Division, Chatrapati Sambhajinagar

Copy to :-The Manager (F&A), EHV O&M Circle, Chatrapati Sambhajinagar.

	Rate inclusing taxes (18% GST and Labour cess 1%)	PAC Inlatrative Bulking M H Can	Diveren, Chamerat sembhar wing No 3. Gears Feet Bhatranseo, 132k/ Hamoni S arsoof, Chamerah Sankungso act Northern, bulkkon s	
	Unit	Each	Each	
	Qt.	-	-	
SCHEDULE A	No Particulars	Godrej make Office Executive TableModel:- Enterprise 1500 Table without CPU Hanger Size 1500 Width mm x 750 Depth mm x 728 Height mm. Specifiction Top shall be 18 mm thick Pvc laminated particle board all work surface edges shall be having duly sealed with 2 mm thick PvC edgebanding. Understructure Modesty Panel 18 mm thick Pre laminated particle board. The Rectangular frame shall be fabricated component in 1.2 mm thick MS ERW ATube, finish powder coat (epoxy polyster). Leg shall be fabricated component in 38 mm x 25 mm 1.2 mm thick MS ERW ATube, finish powder coat (epoxy polyster). The plastic cap for cable travel shall be injection moulded polypropylene and leveler glide for shall be nylon 6 & MS bolt. The storage shall be having shell and drawer tray 0.6 mm thick CRCA Finish powder coat (epoxy polyster) plus lock with 10 lever and handle and leveller. The wire management shall be horizontal wire carrier 0.7 mm thick CRCA Finish powder coat (epoxy polyster) and vertical wire carrier 0.8 mm thick CRCA Finish powder coat (epoxy polyster) The manufacturer shall have Inhouse manufacturing facility and shall have membership/ certification from ISO 9001-QMS, ISO14001 EMS, OHSAS	Godrej make Mid Back ChairModel:- Diva Mid Back ChairSpecification:- The seat and back shall be made from 1.2 ±0.1cm thk. hot pressed plywood measured as per QA method described in OCP-QLTA-P14-18 and shall be upholstered with fabric and moulded Polyurethane foam together with seat and back covers. The back foam shall be designed with contoured lumbar support for extra comfort. The dimensions of seat shall be 45.0cm(W) x 42.0cm.(H). The seat and back covers shall be injection moulded in black Co-polymer Polypropylene. The PR polyurethane foam shall be moulded with density:-45±2.kg/m3 and hardness load 16±2 kg/ as per IS:7888.for 25% compression. The one-piece armrests are injection moulded from black Nylon. The armrests are fitted to the seat with armrest connecting brackets made of 0.5 ± 0.05 em. thk. HR steel. The permanent contact mechanism shall be designed with 360° revolving type, 14±2° maximum back tilt only, Upright position locking. Tilt tension adjustment. The pneumatic height adjustment shall has an adjustment stroke of 11.0 ±0.3cm. The bellow shall be 3 piece telescopic type and injection moulded in black Polypropylene. The pedestal shall be injection moulded in black Polypropylene. The pedestal shall be injection moulded in black Polypropylene. The pedestal shall be 52.0 ±0.5cm. pitch-centre dia. (72.0 ±1.0cm with castors). The twin wheel castors shall be injection moulded in Black Nylon. Overall Dimensions of Chair shall be Seat Height - min 43.0 to max 54.0cm, Height - min87.5 to max 98.5cm, Width & Depth of Chair as measured from pedestal - Width-71.0 cm and Depth-71.0 cm. The manufacturer shall have Inhouse manufacturing facility and shall have membership/ certification from ISO 9001-QMS, ISO14001 EMS, OHSAS 18001, IIID, & BIFMA shall be as directed by Engineer in charge.	Total
	Sr No		N	

Executive Engineer PAC Division, Aurangabad