

MAHARASHTRA STATE ELECTRICITY TRANSMISSION COMPANY LTD (CIN NO- U40109MH2005SGC153646)

Office of the,

Executive Engineer

MSETCL EHV O&M, Division,

Near Market Yard, Bapat Camp, Kolhapur

Tal: - Karvir, Dist-Kolhapur-416 005 E-mail: - ee3210@mahatransco.in

Mobile: - Off-0231-2651529, Fax-0231-2680171

MSETCL/EE/EHV O&M/Dn./Kop/T/LP/742

Date: 25.04.2024

E- Enquiry (Budgetary offer)

Sub: - Enquiry for submission of budgetary offer for supply of T&P (all the material should be of standard make) under EHV O&M DN, Kolhapur.

Dear Sir,

Budgetary offer are invited by the undersigned for supply of T&P under EHV O&M DN, Kolhapur on or before: 03/05/2024 up to 10:00 Hrs. The other terms and conditions are as mentioned below.

1) Quotation should be duly filled in and submitted to this office via post or e-mail ee3210@mahatransco.in

2) This enquiry is solely for collection of offer for estimate purpose & not for work

3) The offer should be submitted as per details mentioned below.

4) Quote rate in prescribed format & Attached Specifications:

5) Details of T&P is attached.

(Aftab Khan) **Executive Engineer** EHV O&M Dn. Kolhapur.

Supply of T&P (all the material should be of standard make) under EHV O&M DN, Kolhapur.

Sr.No	Material Description (All material should be of reputed manufacturer)	Unit	Basic rates	Rates incl of all the taxes
1	Chain pully block & hoist (SWL cap-3/5 ton X 3 mtr heavy duty)	No.		
2	Hook snatch champion pully block single type(single sheave open type cap-swl 3 ton Hook type with safety lock)	No.	-	
3	Hook snatch champion pully block double sheave type (Double sheave pulley block hook type swl cap-3 ton grove)	No.		
4	Automatic come along clamp (wire pulling grip above 150mm to 250mm $\&$ capacity not less than 5 ton) – for 0.2 panther conductor , Liner type	No.		
5	Automatic come along clamp (wire pulling grip above150mm to 250mm & capacity not less than 5 ton) – for 0.2 panther conductor , Liner type	No.		
6	Polypropylene rope bundle (20 mm) Breaking strength-5800kg	No.	nai	
7	Polypropylene rope bundle (24 mm) Breaking strength-8100kg	No.		
8	For line work crimping M/c capacity 100 ton suitable for (0.1, 0.2, 0.4, 0.5 conductor) ACSR twin moose conductor & suitable for 7/3.15 GI earth wire hydraulic pump with DCV manually with min 2 meter hose (Double acting type, operated by any drive like engine, electrical, hand pump sealing method T seal type with MOC test certificate Required by NABL Lab.)	No.		
9	Hydraulic crimping M/c tool suitable for ACSR conductor suitable to crimp (0.1, 0.2, 0.4, 0.5 conductor) Double/ Single acting light weighted, lock pin type both side open jaw type wp-690 bar with suitable hand pump with pressure gauge and unloading valve.	No.		
10	Hook - open type single sheave pulley cap -3 ton	No.		
11	Hook - open type double sheave pulley cap-3 ton	No.		
12	Aluminium foldable ladder - 21 feet	No.		
13	Earthing rod - CPRI or any Govt organization approved with 10Mtr cable	No.		
14	Safety harness with double safety hook (reputed manufacturer)	No.		
15	Flat spanner set along with tool box (reputed manufacturer)	No.		
16	Ring spanner set along with tool box (reputed manufacturer)	No.		
17	Safety helmet (reputed manufacturer) with ISI mark	No.		
18	Grinder machine - Power - 1000 watt toggle switch Support - 4 inch cutting or sanding wheel with 2 meter long cable. material - plastic, metal Protection - Dust & filling Max rotation speed - 10000 RPM Weight - 1.5 Kg	No.		~
19	White Reshm rope polyester rope dia- 18mm Breaking strength-5100kg Plaeena rope 18mm Breaking strength- 21500kg	No.	я	
20	Cutting machine (standard make) Input power - 2400 watt Cutting disc diameter - 355 mm Cutting disc bore - 25.4 mm No load speed - 3800 rpm	No.		,

Sr.No	Material Description (All material should be of reputed manufacturer)	Unit	Basic rates	Rates incl of all the taxes
21	Hammer drill (standards make) -			taxes
	Spec-			
	No load speed - 3000 RPM			
	Concrete drilling diameter - 20/13 mm	No.		
	Masonary drilling diameter - 22/16 mm			
	Steel drilling diameter - 13/8 mm			
22	Rachet set (standard make)			
22	Material - Chrome vandalium steel	No.		
	Size - 8 mm to 32 mm			
	Portable Welding Machine (standard make)- 200 A Stud Type Welding			
	Machine Single Phase and Double Phase Input voltage: 220V ±15%			
	Frequency: 50 Hz			
	Rated input power: 7.3 KVA			
	Current range: 20–200A			-V-1
	Permitted load at 60% duty cycle: 200A		152 40	
23	Power factor (max): 0.9	No.	-	
	Efficiency at maximum current: 85%	110.		
	Arc force: Adjustable			
	Error indicator: Yes			
	Power indicator: Yes			
	Weight: 8 kg		_	
	Recommended electrode size: Up to 4.00 mm			
-	Jigsaw machine			
	Input power - 780W			
	Cable length - min 4 meter	200		
	Stroke rate at no load - 500 -3100 SPM	No.		
	Wt - 2.5 kG			
	Hot stick suitable for 220kV and 110kV (Epoxy glass / glass fiber (
25	reinforced) as per the IS standard.	No.		
26	Hydraulic ladder lift extendable up to 30 feet	No.		
27	FRP extendable ladder up to 20 feet	No.		